Stainless Metal Craft (Aust) Pty Ltd
ABN 31 003 951 004
Bldg 2, 6 Bromley Road
EMU PLAINS NSW 2750
Phone: + 61 2 4735 5666
Fax: + 61 2 4735 7950

Installation Instructions and User's Guide – Clay/Plaster Trap CA-1

This Clay/Plaster Trap has been designed and approved by Water Board Authorities. When installed and maintained properly, this unit will give many years of service and help protect our Environment.

THE PLUMBER

- Locate the Clay/Plaster Trap in a position that provides a minimum of 250mm clearance from lid to underside of bench top for removal of lid and inner filter basket
- Connect 50mm trap to sink bowl and inlet on the CA-1 and ensure water level of trap is a minimum of 200mm above water level of Clay/Plaster Trap.
- Test all connections for leaks

THE USER

- Do not dispose of acids, chemicals or any other substance unsuitable for normal sink waste through this trap
- Do not dispose of large quantities of Plaster/Clay through this Trap
- When washing down implements used, ensure enough water is used to clear the "S" trap connection to Clay/Plaster Trap
- Maintenance will depend on usage – a trap used daily with high volumes of clay/plaster will require more frequent cleaning
- Empty basket and flush out trap and tank if left in an unused state for long periods of time (eg School Holidays etc)

MAINTENANCE INSTRUCTIONS

- Remove lid from Clay/Plaster Trap
- Push inner basket tank away from inlet
- Remove inner basket tank from trap
- Remove wave/filter screens and clean
- If the Clay/Plaster Trap itself needs cleaning, drain the tank before disconnection, then remove the tank and clean as require and reconnect. Refer to Installation Instructions.

www.smcstainless.com.au
info@smcstainless.com.au